



REACH & RoHS
COMPLIANT

REV.	ECN / DESCRIPTION	BY	DATE
A0	NEW	MQ.Cui	2023.03.02



ELECTRICAL CHARACTERISTICS: (TRUE V.34 FOR PCMCIA)

1. D.C.R. PIN 1-3 = 136 OHM +/-10% PIN 4-6 = 128 OHM +/-10%
2. INDUCTANCE (@250HZ, 0.5Vrms, PARALLEL) 1-3 = 3.9H MIN.
3. IMPEDANCE (@ 1KHZ, 0dBm, 6-4 W/H 348 OHM)
1-3 = 600 OHM +/-2%
4. INSERTION LOSS = 2.6 +/-0.1dB
(AT 1KHZ, 0dBm, W/H 348 OHM LOAD)
5. FREQ. RESP. (@ 300HZ TO 4KHZ, REF. 1KHZ) = +/-0.1dB
6. RETURN LOSS @300HZ = 30dB MIN. @1KHZ = 35dB MIN.
@4KHZ = 35dB MIN.
7. TURN RATIO = 1:1 +/-1%
8. POLARITY = PIN 1-6 INPHASE
9. LONGITUDINAL BAL. = 70dB MIN. (@ 200HZ TO 4KHZ)
10. T.H.D. (@600HZ, -10dBm) = -82dB MAX.
11. HI-POT = 1250 VAC, 1mA, 2SEC. (PRI.-SEC.)



苏州沃虎电子科技有限公司

Tel:4001048018 Http://www.wohu-tek.com

Part Number	Impedance PRI:SEC	Type&Size	Mounting	Hi-Pot (Vrms)	Inductance	Turns Ratio (Line:Device)	Dimension L/W/H(mm)
ATS-168	600:348	EL-08	SMD(Low profile)	1250	3.9H Min	1:1	14/8.0/4.6